

Architectural Specification Sheet



The XGT(Super GT) Series is manufactured by PDQ Industries, Inc. Leola, Pennsylvania and is assembled in the U.S.A, meeting the requirements of the Buy American Act.. with a limited lifetime manufacturer's warranty, and certified to ANSI/BHMA A156.2-1996, Series 4000, Grade 1. Windstorm Resistant Product Listed - ANSI A250. 13-2003, ASTM E1886-02, ASTM E330-02. Outswing: 350 ft-lbs., Inswing: N/R, Design Load Rating: 1485 lbf. Locksets shall be listed by U.L./U.L.C. for ratings of "A" (3 hours) label and less, for single doors up to 4'0" x 8'0". Levers to be solid cast, with no plastic inserts, minimum 5-1/2" overall length with supportive spring power totally independent of chassis or latch unit. Latchbolt to be minimum 9/16" throw and requires only 41° rotation of levers for full retraction. Lockset fasteners to be concealed with through-the-door through-bolt attachment outside the 2-1/8" door prep, exceeds 3000 in lbs. of torque resistance.



SPECIFICATIONS – XGT SERIES

FOR DOORS: 1-3/4" to 2-1/4" thick. Factory adjusted for 1-3/4".
DOOR PREP: Fits standard 161 door prep. Through-door thru-bolting.
BACKSET: 2-3/4" only. Guarded.
CASE: Heavy duty zinc diecast hubs, chromated cold rolled steel, stainless Steel and Zamak 5 mechanism. Billet steel spindles.
High strength stainless steel investment cast locking tip.
FRONT: Stainless steel or wrought brass. 2-1/4" x 1-1/8". Beveled 1/8" on 2".
ROSE: 3-3/8" diameter.
STRIKE: 4-7/8" x 1-1/4" (ASA). "T" or "FL" Strike optional. Stainless steel or wrought brass.
LATCHBOLT: 9/16" Throw. Adjustable front for flat or beveled doors.
HAND: Non-handed.
TRIM: PHL, BSN or MIA levers are solid zinc diecast. 41P lever rotation.
Wrought brass roses. Concealed screws.
High strength stainless steel investment cast spindle.
Heavy gauge steel mounting plates.
KEYS: Two (2) change keys per lock.
KEYWAYS: Available in keyways of most major manufacturers.

INTERCHANGEABLE

CORE: Available for all keyed functions. 6 or 7 pin.
CYLINDER: Brass 6-pin cylinder keyed to 5 pins.
KEYING: Can be MK, CMK, GMK. Available Zero Bitted (K0), Keyed Different (KD), Keyed Alike (KA). Can be keyed into existing Masterkey systems of other manufacturers.
FINISHES: US3(605), US4(606), US10(612), US10B(613), US26(625), US26D(626) US17A(621).
CERTIFICATIONS: ▶ BHMA Certified Product
ANSI/BHMA A156.2-1996, Series 4000, Grade 1. Windstorm Resistant Product Listed - ANSI 250. 13-2003, ASTM E1886-02, ASTM E330-02, Outswing: 350 ft-lbs., Inswing: N/R, Design Load Rating: 1485 lbf.
▶ Meets all accessibility requirements of the ADA.
▶ U.L./U.L.C. Listed for "A" label (3 hour) single swing doors (4'0" x 8'0").
▶ Exceeds 3000 in. lbs. of torque resistance.
▶ Certification through ETL.
Lifetime Limited warranty.
WARRANTY:
COUNTRY OF ORIGIN: Assembled in the U.S.A., of US and foreign material, this product meets the requirements of Buy American Act.